





KEY FEATURES

- This swivel bi-fold operator throws locking bolts into the frame at top and bottom of the panel. Optional key-locking (separately installed) is available.
- Having an operator handle located centrally on say a bi-fold door removes the need to bend down or stretch to reach flush bolts that might be located at the ends of the stiles.
- The MIRO™ handle is curved with no visible fasteners when handle is in closed position.
- Furniture available in a large range of powder coat finishes to match the door panel colour.
- Matching hinged door lever furniture.




FINISHING

MIRO™ bi-fold operator can be supplied non-key locking or with key-locking. The furniture is available in a range of standard or special colours.




ADJUSTABLE KEEPERS

On Series 410 Bi-fold doors the keeper in head and sill is adjustable. This allows the panels to be tightened on the frame.



SUPPORT

Bolt tips are supported by extruded aluminium guides. Ensures the bolts fall in the right location and can withstand high wind loads.



STRENGTH

Elevate™ commercial strength bi-fold doors are assembled with heavy duty extruded aluminium spigots and backing plates.

DIMENSIONS

Height	158mm
Width	30mm
Depth	16mm


SUITABLE FOR USE WITH

- Series 618 MAGNUM™ Sliding Door
- Series 731 ThermalHEART® Sliding Door
- Series 702 SlideMASTER™ Sliding Door
- Series 704 SlideMASTER™ Sliding Door




KEY FEATURES

- The MIRO™ Casement Latch is designed to suit residential, architectural and Elevate™ commercial awning and casement windows.
- This fastener is curved similar to a gum leaf.
- Available in a range of standard or special powder coat finishes.
- The retention wedge folds up to cam lever when opened. This is a significant feature in that there is no fixed keeper on the frame.
- Matching hinged door lever furniture.




CASEMENT COMPATIBLE

MIRO™ cam latch can be fitted to awning and casement sashes. The latch is available left or right hand.




STRENGTH

We offer a range of heavy duty sashes that can be fabricated in large sizes and are supported on heavy duty four bar friction stays.



CUSTOM SUB-SILL

Elevate™ Commercial awning windows are fitted into custom sub-sill. This sub-sill is designed to go into residential installations.



WATERPROOF

Elevate™ awning and casement sashes are fabricated with heavy duty nylon corner stakes. These keep the joints tight and waterproof.

DIMENSIONS

Height	35mm
Width	125mm
Depth	44mm

SUITABLE FOR USE WITH

- Series 516 Residential Awning/Casement Window
- Series 517 Residential Awning/Casement Window
- Series 616 MAGNUM™ Awning/Casement Window
- Series 726 ThermalHEART® Awning/Casement Window
- Series 456 Commercial Awning Window
- Series 466 Architectural Awning/Casement Window




KEY FEATURES

- With a sleek, comfortable grip common to all MIRO™ hardware, the lever door lock is available in several locking options, including keyed both sides or with interior snib.
- Used in conjunction with lever compression locking, an upward handle movement activates four-point locking.




FINISHING

MIRO™ hinged lock is available in a range of powder coated colours.



DUMMY LOCK

The dummy lock can be operated from inside, the handle retracts the shoot bolts top and bottom.



SHOOT BOLTS

Shoot bolts on non-thermal commercial doors fitted with multi-point locks shown.



CUSTOM DESIGNED

We offer offer three custom furniture sets ICON™, MIRO™ and ANDO™, all three are distinctly different.

DIMENSIONS

Height	211mm
Width	130mm
Depth	70mm

SUITABLE FOR USE WITH

- Series 549 Residential Entry Door
- Series 548 Designer Bi-fold Door
- Series 548 Designer Hinged Door
- Series 729 ThermalHEART® Hinged Door

- Series 730 ThermalHEART® Bi-fold Door
- Series 410 FoldMASTER™ Bi-fold Door
- Series 650 Architectural Hinged Door